


TECHNICAL DATA SHEET

| FABRIC DETAILS | | | |
|---------------------------|------|---------------|------|
| Composition: | | | |
| Weight g/m: | | Width: | |
| Weight g/m ² : | | Usable width: | |
| Weave: | | Density: | |
| | WARP | | WEFT |
| Yarn count: | | | |

| COLOUR FASTNESS | | REFERENCE | COLOR CHANGE | STAIN | | | | | |
|-------------------------|---------|-----------|-----------------------|-----------------------------|---|---|-----------------------------|----|---|
| | | | | A | C | N | P | AC | W |
| To washing: | | | | | | | | | |
| To dry cleaning: | | | | | | | | | |
| To perspiration: | Acid | | | | | | | | |
| | Alcalic | | | | | | | | |
| | | | | WARP | | | WEFT | | |
| To dry rubbing: | | | | | | | | | |
| To wet rubbing: | | | | | | | | | |
| | | | COLOUR CHANGE AT ONCE | COLOUR CHANGE AFTER 4 HOURS | | | STAINING ON COTTON ADJACENT | | |
| To hot pressing | Dry | | | | | | | | |
| | Damp | | | | | | | | |
| | Wet | | | | | | | | |
| To non-chlorine bleach: | | | | | | | | | |
| To light: | | | | | | | | | |

A - acetate C - cotton N - nylon P - polyester AC - acrylic W - wool

| CARE INSTRUCTION | | REFERENCE | COLOR | PILING | DEFECTS | CONCLUSION |
|--------------------------------|--------------------|--|-------|--------|---------|------------|
| Appearance after washing: | After one wash | | | | | |
| | After three washes | | | | | |
| Appearance after dry cleaning: | | | | | | |
| Care pictograms: | |  | | | | |

| PACKING | | | |
|--------------|--|-----------|--|
| Roll length: | | Wrapping: | |

| | |
|------------------|--|
| HS customs code: | |
|------------------|--|

JÓŹWIĄK S.C.

Narcykowa 24, PL-60175 Poznań, Wielkopolskie, Polska
 VAT: PL7792295976 / REGON: 300419818

T: +48 61 867 75 14 / F: +48 61 867 80 65
 jozwiak@jozwiak.eu / www.jozwiak.eu

TECHNICAL DATA SHEET

| PHYSICAL PROPERTIES | | REFERENCE | WARP | | | | WEFT | | | | |
|--|-------------------------------|-----------|------------|-----|-----------|------|------------|------|-----------|--|------------|
| Seam slippage: | Seam opening at 6mm | | | | | | | | | | |
| | Seam strenght | | | | | | | | | | |
| Dimensional stability to washing: | | | | | | | | | | | |
| Dimensional stability to dry cleaning: | | | | | | | | | | | |
| Dimensional stability to steam: | | | | | | | | | | | |
| Tear strenght: | | | | | | | | | | | |
| Tensile strenght: | | | | | | | | | | | |
| Elongation: | | | | | | | | | | | |
| | | | CYCLES | | | | | | | | |
| | | | 125 | 500 | 1000 | 2000 | 5000 | 7000 | 10800 | | |
| Pilling: | | | | | | | | | | | |
| | | | Elongation | | UN (1min) | | UN (30min) | | RE (1min) | | RE (30min) |
| Stretch properties: | Warp | | | | | | | | | | |
| | Weft | | | | | | | | | | |
| | Length - specified load | | | | | | | | | | |
| | Width - specified load | | | | | | | | | | |
| | Length - specified elongation | | | | | | | | | | |
| | Width - specified elongation | | | | | | | | | | |
| Spirality: | After drycleaning | | | | | | | | | | |
| | After laundering | | | | | | | | | | |
| Abrasion resistance: | | | | | | | | | | | |

FB - Fabric Broken STB - Sewing Thread Broken FBS - Fabric Broken at Seam YPO - Yarn Pull Out UN - Unrecovered Elongation RE - Recovered Elongation
 X - The Seam Opening was less than 6mm, though the ultimate steam strenght was founded as stated Cross Tear - means the force does not proceed along the direction of force